

**UNITEDPOWER**

HISTORY IN ENGINEERING EXCELLENCE

STAINLESS STEEL FLEXIBLE CONDUIT

SPECIFICATION :

- ✓ AVAILABLE SS GRADE : 202 / 304 / 316
- ✓ HIGH MECHANICAL STRENGTH.
- ✓ FLEXIBLE
- ✓ TEMPERATURE RANGE : - 100 DEGREE C TO +300 ETC.) DEGREE C
- ✓ IP RATING : IP40 (GRADE : 316)

APPLICATION :

- ✓ MACHINE TOOLS.HIGH MECHANICAL STRENGTH.
- ✓ OUTDOOR INSTRALLATIONS.
- ✓ USED AS MECHANICL PROTECTION FOR INSULATED
- ✓ ELECTRICAL CABLE & WIRES THAT ARE FINCTIONAL IN
- ✓ NORMAL ATMOSPHERIC TEMPERATURE.
- ✓ UNDER FLOOR APPLICATION FOR COMPUTER / FLOOR BOXES.
- ✓ ELEVATORS, METRO STATIONS, CCTV CAMERA ETC.



BRITISH STANDARD

Cat.#	Size	Internal Diameter (mm)	External Diameter (mm)	Min. Bend Radiuce (mm)	Coil Packing (m)
SSFC-BS-16	16mm	13	16	30	15-20-25-30
SSFC-BS-20	20mm	16.9	20.5	30	15-20-25-30
SSFC-BS-25	25mm	21.1	25	43	15-20-25-30
SSFC-BS-30	30mm	28.1	32	50	15-20
SSFC-BS-40	40mm	37.6	42.5	57	10-15
SSFC-BS-50	50mm	48.4	53	70	10-15
SSFC-BS-63	63mm	57.5	62.5	115	7.5-10
SSFC-BS-75	75mm	70	77	150	7.5-10

INDIAN STANDARD

Cat.#	Size	Internal Diameter (mm)	External Diameter (mm)	Min. Bend Radiuce (mm)	Coil Packing (m)
SSFC-IS-3/8	3-8"	10	13	30	15-25-30
SSFC-IS-1/2	1/2"	13	17	43	15-25-30
SSFC-IS-5/8	5-8"	16	19	30	15-25-30
SSFC-IS-3/4	3/4"	19	23	50	15-25-30
SSFC-IS-1	1	25	29	57	15-25-30
SSFC-IS-1-1/4	1¼"	32	36	70	15-25-30
SSFC-IS-1-1/2	1½"	38	43	80	15-25-30
SSFC-IS-2	2"	50	55	95	15-25-30
SSFC-IS-2-1/2	2½""	63	70	140	7.5-15
SSFC-IS-3	3"	78	85	150	7.5-15
SSFC-IS-4	4"	101	109	190	7.5-15

AMERICAN STANDARD

Cat.#	Size	Internal Diameter (mm)	External Diameter (mm)	Min. Bend Radiuce (mm)	Coil Packing (m)
SSFC-US-3/8	3/8"	12.5	16	30	50
SSFC-US-1/2	1/2"	16	19.2	43	30
SSFC-US-3/4	3/4"	20.4	24.8	50	30
SSFC-US-1	1	26.6	30.8	57	30
SSFC-US-1-1/4	1¼"	35	40	70	15
SSFC-US-1-1/2	1½"	40.3	45.4	80	15
SSFC-US-2	2"	51.5	56.8	95	15
SSFC-US-2-1/2	2½"	63.3	70.6	140	7.5
SSFC-US-3	3"	78.4	85.5	150	7.5
SSFC-US-4	4"	102	112	190	7.5

GERMANY STANDARD

Cat.#	Size	Internal Diameter (mm)	External Diameter (mm)	Min. Bend Radiuce (mm)	Coil Packing (m)
SSFC-PG-7	PG7	9.4	12.7	30	50
SSFC-PG-9	PG9	10.7	14.1	35	30
SSFC-PG-11	PG11	13.8	17	38	30
SSFC-PG-13	PG13	15.7	19.7	40	30
SSFC-PG-16	PG16	17.4	21.5	45	15
SSFC-PG-21	PG21	22.7	27.4	50	15
SSFC-PG-29	PG29	31	36	58	15
SSFC-PG-36	PG36	39.7	46	90	7.5
SSFC-PG-48	PG48	51.2	57.5	100	7.5

40- A, Milind Kibe Colony Near Kamla Nehru School, Indore - 452001, Madhya Pradesh, India

9826086180, 9300000151 up.unitedpower@gmail.com www.metalflexibleconduit.com